













# kudret

Tuğla Sanayi ve Tic. A.Ş.



## 2009 Price List

### C - CLAYMIX® "Insulation Brick" and CLAYFIX® "Leightweight Mortar"

 <p>11,5 cm CLAYMIX (Class UL-W )</p> <p>Amounty of mortar needed per m2 : 4,5 Kg</p>	Type(TS EN 771-1)	Category II – LD	 <p>14,5 cm CLAYMIX (Class UL-W )</p> <p>Amounty of mortar needed per m2 : 6 Kg</p>	Type(TS EN 771-1)	Category II – LD
	Diameters (cm.)	24*11,5*23,5		Diameters (cm.)	24*14,5*23,5
	<b>FOB Price</b>	<b>0,36 €</b>		<b>FOB Price</b>	<b>0,40 €</b>
	Unit/Pallet	180		Unit/Pallet	140
	Wall Thickness	11,5 cm.		Wall Thickness	14,5 cm.
	Consumption/m2	16,5		Consumption/m2	16,5
	Weight (kg.)	4,50		Weight (kg.)	5,50
	Compr. Strenght	7,5 N/mm2		Compr. Strenght	7,5 N/mm2
	Thermal Conductivity	0,18 W/mK		Thermal Conductivity	0,18 W/mK
	Density	700 Kg./m3		Density	700 Kg./m3
 <p>17,5 cm CLAYMIX (Class UL-W )</p> <p>Amounty of mortar needed per m2 : 6,5 Kg</p>	Type(TS EN 771-1)	Category II – LD	 <p>19 cm CLAYMIX (Class UL-W )</p> <p>Amounty of mortar needed per m2 : 7 Kg</p>	Type(TS EN 771-1)	Category II – LD
	Diameters (cm.)	24*17,5*23,5		Diameters (cm.)	29*19*23,5
	<b>FOB Price</b>	<b>0,45 €</b>		<b>FOB Price</b>	<b>0,63 €</b>
	Unit/Pallet	140		Unit/Pallet	100
	Wall Thickness	17,5 cm.		Wall Thickness	19 cm.
	Consumption/m2	16,5		Consumption/m2	13,5
	Weight (kg.)	6,50		Weight (kg.)	9,00
	Compr. Strenght	7,5 N/mm2		Compr. Strenght	7,5 N/mm2
	Thermal Conductivity	0,18 W/mK		Thermal Conductivity	0,18 W/mK
	Density	700 Kg./m3		Density	700 Kg./m3
 <p>24 cm CLAYMIX (Class UL-W )</p> <p>Amounty of mortar needed per m2 : 9 Kg</p>	Type(TS EN 771-1)	Category II – LD	 <p>30 cm CLAYMIX (Class UL-W )</p> <p>Amounty of mortar needed per m2 : 10 Kg</p>	Type(TS EN 771-1)	Category II – LD
	Diameters (cm.)	24*24*23,5		Diameters (cm.)	24*30*23,5
	<b>FOB Price</b>	<b>0,69 €</b>		<b>FOB Price</b>	<b>0,76 €</b>
	Unit/Pallet	100		Unit/Pallet	90
	Wall Thickness	24 cm.		Wall Thickness	30 cm.
	Consumption/m2	16,5		Consumption/m2	16,5
	Weight (kg.)	9,50		Weight (kg.)	11,50
	Compr. Strenght	7,5 N/mm2		Compr. Strenght	7,5 N/mm2
	Thermal Conductivity	0,18 W/mK		Thermal Conductivity	0,18 W/mK
	Density	700 Kg./m3		Density	700 Kg./m3
 <p>19 x 24 cm CLAYMIX (Class UL-W )</p> <p>Amounty of mortar needed per m2 : 7,5 Kg</p>	Type(TS EN 771-1)	Category II – LD	 <p>20 CLAYMIX Honeycomb Cell (Class UL- W )</p> <p>Amounty of mortar needed per m2 : 8 Kg</p>	Type(TS EN 771-1)	Category II – LD
	Diameters (cm.)	24*19*23,5		Diameters (cm.)	25*20*23,5
	<b>FOB Price</b>	<b>0,53 €</b>		<b>FOB Price</b>	<b>0,54 €</b>
	Unit/Pallet	115		Unit/Pallet	115
	Wall Thickness	19 cm.		Wall Thickness	20 cm.
	Consumption/m2	16,5		Consumption/m2	16,5
	Weight (kg.)	7,00		Weight (kg.)	7,50
	Compr. Strenght	7,5 N/mm2		Compr. Strenght	7,5 N/mm2
	Thermal Conductivity	0,18 W/mK		Thermal Conductivity	0,18 W/mK
	Density	700 Kg./m3		Density	600 Kg./m3
 <p>25 CLAYMIX Honeycomb Cell (Class UL-W )</p> <p>Amounty of mortar needed per m2 : 8,5 Kg</p>	Type(TS EN 771-1)	Category II – LD	 <p>30 cm - V.P.B Honey Comb Cell (Class UL-W )</p> <p>Amounty of mortar needed per m2 : 10 Kg</p>	Type(TS EN 771-1)	Category II - LD
	Diameters (cm.)	25*25*23,5		Diameters (cm.)	24*30*23,5
	<b>FOB Price</b>	<b>0,68 €</b>		<b>FOB Price</b>	<b>0,74 €</b>
	Unit/Pallet	100		Unit/Pallet	90
	Wall Thickness	25 cm.		Wall Thickness	30 cm.
	Consumption/m2	16,5		Consumption/m2	16,5
	Weight (kg.)	8,50		Weight (kg.)	10 kg.
	Compr. Strenght	7,5 N/mm2		Compr. Strenght	7,5 N/mm2
	Thermal Conductivity	0,16 W/mK		Thermal Conductivity	0,16 W/mK
	Density	600 Kg./m3		Density	600 Kg./m3

ClayMix bricks' prices include lightweight perlite mortar price. ClayFix lightweight perlite mortar and mortar gauges are given with the bricks without extra payment. Specific consumption of the mortar for a partical brick has been shown on this price list.