










kudret

Tuğla Sanayi ve Tic. A.Ş.



2009 Price List

D- VERTICALLY PERFORATED and LOAD BEARING(HD) BRICKS (TS EN 771-1) CE

 19 cm. V.P.B. Height 13,5 cm	Type (TS EN 771-1)	Category II - LD	 24 cm. V.P.B. Height 13,5 cm	Type (TS EN 771-1)	Category I - LD
	Diameters (cm.)	29*19*13,5(h)		Diameters (cm.)	29*24*13,5(h)
	FOB Price	0,23 €		FOB Price	0,30 €
	Unit/Pallet	198		Unit/Pallet	162
	Wall Thickness	19 cm. - 29 cm.		Wall Thickness	24 cm. - 29 cm.
	Consumption/m2	(22 - 35)		Consumption/m2	(22 - 31)
	Weight (kg.)	5,00		Weight (kg.)	6,50
	Compr. Strenght	10 N/mm2		Compr. Strenght	10 N/mm2
	Thermal Conductivity	0,32 W/mK		Thermal Conductivity	0,32 W/mK
	Density	700 kg./m3		Density	700 kg./m3
 19 cm. High Type V.P.B. Height : 19 cm	Type (TS EN 771-1)	Category II - LD	 19 cm. DECORATIVE BRICK (Feasible Without Plasters) Height 13,5 cm	Type (TS EN 771-1)	Category I - HD
	Diameters (cm.)	29*19*19(h)		Diameters (cm.)	29*19*13,5
	FOB Price	0,37 €		FOB Price	0,27 €
	Unit/Pallet	132		Unit/Pallet	198
	Wall Thickness	19cm. - 29cm.		Wall Thickness	19 cm.
	Consumption/m2	18 - 25		Consumption/m2	-22
	Weight (kg.)	8,00		Weight (kg.)	5,50
	Compr. Strenght	10 N/mm2		Compr. Strenght	10 N/mm2
	Thermal Conductivity	0,32 W/mK		Thermal Conductivity	0,37 W/mK
	Density	700 kg./m3		Density	800 kg./m3
 19 cm. DECORATIVE BRICK (Feasible Without Plasters) Height : 19 cm	Type (TS EN 771-1)	Category II - HD	 19 x 39 cm V.P.B. Height 13,5 cm	Type (TS EN 771-1)	Category II - LD
	Diameters (cm.)	29*19*19(h)		Diameters (cm.)	39*19*13,5(h)
	FOB Price	0,39 €		FOB Price	0,39 €
	Unit/Pallet	132		Unit/Pallet	135
	Wall Thickness	19cm.		Wall Thickness	19 cm.
	Consumption/m2	18		Consumption/m2	16,5
	Weight (kg.)	5,50		Weight (kg.)	7,50
	Compr. Strenght	10 N/mm2		Compr. Strenght	8 N/mm2
	Thermal Conductivity	0,37 W/mK		Thermal Conductivity	0,32 W/mK
	Density	800 kg/m3		Density	750 kg./m3
 High Type 19 x 39 cm V.P.B. Height : 19 cm	Type (TS EN 771-1)	Category II - LD	 TAŞIYICI YIĞMA Height 13,5 cm	Type (TS EN 771-1)	Category I - HD
	Diameters (cm.)	39*19*19(h)		Diameters (cm.)	29*19*13,5(h)
	FOB Price	0,57 €		FOB Price	0,43 €
	Unit/Pallet	90		Unit/Pallet	198
	Wall Thickness	19 cm.		Wall Thickness	19cm. -29 cm.
	Consumption/m2	12,5		Consumption/m2	(22 - 35)
	Weight (kg.)	11,00		Weight (kg.)	8,50
	Compr. Strenght	8 N/mm2		Compr. Strenght	14 N/mm2
	Thermal Conductivity	0,32 W/mK		Thermal Conductivity	0,50 W/mK
	Density	750 kg./m3		Density	1100 kg./m3
 Moduler Type Decorative Brick Height : 8,5 cm	Type (TS EN 771-1)	Category II - HD	 High Type Moduler Decorative Brick Height 13,5 cm	Type (TS EN 771-1)	Category II - HD
	Diameters (cm.)	19*9*8,5(h)		Diameters (cm.)	19*9*13,5(h)
	FOB Price	0,13 €		FOB Price	0,20 €
	Unit/Pallet	848		Unit/Pallet	560
	Wall Thickness	9 cm.		Wall Thickness	9 cm.
	Consumption/m2	62 Adet		Consumption/m2	35 Adet
	Weight (kg.)	1,60		Weight (kg.)	2,50
	Compr. Strenght	14 N/mm2		Compr. Strenght	14 N/mm2
	Thermal Conductivity	0,50 W/mK		Thermal Conductivity	0,50 W/mK
	Density	1100 kg./m3		Density	1100 kg./m3

Brick weights may change around + -%5